查询2SA1216供应商

2SA1216 PNP PLANAR SILICON TRANSISTOR

AUDIO POWER AMPLIFIER
DC TO DC CONVERTER

- High Current Capability
- High Power Dissipation
- Complementary to 2SC2922

MT-200



ABSOLUTE MAXIMUM RATING (Ta=25℃)

Characteristic	Symbol	Rating	Unit
Collector-Base Voltage	VCBO	-180	V
Collector-Emitter Voltage	VCEO	-180	V
Emitter-Base voltage	VEBO	-6	V
Collector Current (DC)	IC	-17	A
Collector Dissipation	PC	200	W
Junction Temperature	Tj	150	℃
Storage Temperature	Tstg	-50~150	℃

ELECTRICAL CHARACTERISTICS (Ta=25℃)

Characterristic	Symbol	Test Condition	Min	Typ	Max	Unit
Collector Base Breakdown Voltage	BVCBO	IC=-10 mA IE=0	-180			V
Collector Emitter Breakdown Voltage	BVCEO	IC=-5 mA RBE=∞	-180			V
Emitter Base Breakdown Voltage	BVEBO	IE=-4mA IC=0	-6			V
Collector Cutoff Current	ICBO	VCB=-90V IE=0			-0.1	mA
Emitter Cutoff Current	IEBO	VEB=-4V IC=0			-0.1	mA
*DC Current Gain	hFE1	VCE=-5V IC=-1A	50		150	
DC Current Gain	hFE2	VCE=-4V IC=-8A	30			
Collector- Emitter Saturation Voltage	VCE(sat)	IC=-8A IB=-0.8A			-2.0	V

Wing Shing Computer Components Co., (H.K.)Ltd. Tel:(852)2341 9276 Fax:(852)2797 8153
Homepage: http://www.wingshing.com E-mail: wsccltd@hkstar.com